

Wall Mounted Multi-Gas Detector Alarming

The products are widely used in metallurgy, chemical industry, petroleum, pharmaceutical, environmental industries work environment with toxic and harmful gas or oxygen content detection, up to four gas detection at the same time, using imported sensors, high precision, strong anti-interference ability, long service life, live shows, sound and light alarm, intelligent design, simple operation, easy calibration, zero, alarm Settings, can be output relay control signals, metal shell, strong and durable, convenient installation.

Optional RS485 output module, easy to connect with DCS and other monitoring center.



Product Parameters

Sensor: Combustible gas is catalytic type, other gases are electrochemical, except special
Responding time: EX ≤ 15s; O ₂ ≤ 15s; CO ≤ 15s; H ₂ S ≤ 25s
Work pattern: continuous operation
Display: LCD display
Screen Resolution: 128*64
Alarming mode: Audible & Light, Light alarm -- High intensity strobes Audible alarm -- above 90dB
Output control: relay output with two way (normally open, normally closed)
Storage: 3000 alarm records
Digital interface: RS485 output interface Modbus RTU (optional)
Backup power supply: provide power outage for more than 12 hours (optional)
Working power supply: AC220V, 50Hz
Temperature range: -20°C ~ 50°C
Humidity range: 10 ~ 90% (RH) No condensation
Installing mode: wall-mounted installing
Outline dimension: 203mm × 334mm × 94mm
Weight: 3800g